STARKE

DIESEL HAMMER SERIES

HD8-HD220

INTELLIGENT MANUFACTURER OF PILING EQUIPMENT

STARKE Full of Might.

Diesel Hammer HD8-HD220

High striking energy

High cost performance

Easy operati on

Simple mal ntenance

Convenient transportation

Precision all around.

Diesel Hammer HD8-HD220

Structure

HD8-HD220

Diesel hammer

Technical Parameters

MODEL	UNIT	HD8	HD12	HD19	HD25	HD30	HD35	HD45	HD50	HD62	HD72	HD90	HD100	HD125	HD150	HD180	HD220
Impact weight (upper piston)	kg	800	1280	1920	2500	3000	3600	4600	5000	6200	7200	8000	10000	12500	16000	18000	22000
Power per stroke	kNm	27.2 12.8	43.52 20.48	61.88 29.43	85 39.2	103.32 48.51	112.9 56.5	156.4 72.13	180 80	217 108.5	244.8 122.4	272 176	340 220	425 275	516.8 348.8	630 450	770 550
Number of strokes		35 52	35 52	35 52	35 52	35 52	35 52	35 52	35 52	35 50	35 50	36 45	36 45	36 45	36 45	37 45	37 45
Maximum explosive force on pile	kN	505	606	686	1304	1304	1695	1695	1770	1800	1800	2600	2600	3395	4485	4500	5900
Max. weight for suitable pile	kg	3000	5000	6000	7000	8000	10000	15000	20000	25000	27000	30000	40000	50000	70000	80000	85000
Max. steel rope diameter for trip gear	mm	≠20	≠20	≠20	≠22	≠22	≠25	≠25	≠25	≠25	≠25	≠25	≠30	≠30	≠38	≠38	≠38
FUEL CONSUMPTION																	
Diesel (max)	L/h	3.8	5.0	6.5	9.1	10.1	12.6	16.6	16.6	19.1	20.4	26	29	43	50	53	65
Lubricating oil (max)	L/h	2.6	2.6	2.6	2.6	2.6	3.0	3.0	3.0	3.0	3.0	5.0	5.0	5.0	5.0	5.0	5.0
VOLUME																	
diesel tank	L	31.5	34.5	37.5	63.5	63.5	83	83	81	96	96	129	129	185	300	290	400
Lubricating oil tank (max)	L	8.2	10	10	17.5	17.5	17	17	20.9	29.5	29.5	43.5	43.5	75.5	75.5	80	90
WEIGHT																	
Trip gear (approx.)	kg	160	160	160	175	175	600	600	600	600	600	1170	1170	1170	2200	2500	2500
Hammer (approx.)	kg	2050	3110	3750	5556	6050	8200	10200	11400	12300	12700	16900	20560	25500	32800	38000	47000
DIMENSIONS																	
Height of hammer (a)	mm	4418	4450	4700	4910	4910	5270	5270	5560	5990	5990	6220	6220	6383	7115	7145	7390
Height of hammer with lengthen cylinder (a1)	mm	4970	5000	5300	5410	5410	5770	5770	/	6490	6490	6720	6720	6963	7465	7845	7760
Max. outer diameter of lower piston (b)	mm	≠350	≠440	≠440	≠560	≠560	≠660	≠660	≠670	≠710	≠710	≠810	≠810	≠910	≠990	≠1060	≠1180
Max. horizontal width of hammer (c)	mm	625	625	625	700	700	930	930	1002	980	980	1100	1100	1185	1380	1580	1580
Central distance between hammer and hammer guide screw (d)	mm	200	280	280	235	235	275	275	320	380	380	350	350	370	380/460	/	/
Max. vertical height of hammer (e)	mm	730	770	795	930	930	1030	1030	1120	1130	1130	1376	1376	1485	1670	2000	2000
Central distance of lead guide (g)	mm	370	395	405	485	485	530	530	544	560	560	720	720	780	830	1050	1050
Central distance of between hammer center and protector board / diesel pump (h)	mm	330	330	330	330	330/600	330/600	330/600	330/600	330/600	330/600	600	600	600	600	1000	1000
Distance between hammer center and protector board / diesel pump (h)	mm	306	327	337	380	380	440	440	460	480	480	495	495	560	620	/	/
Max. length of stroke of upper piston	mm	3573	3492	3734	3842	3842	3693	3693	4029	4518	4518	4110	4110	4556	5010	5280	5280

Diesel Hammer

Strong Adaptability.

Applicapable Pile Types

Pile caps can be customized according to the actual needs of customers.

Diesel Hammer

Matching Piling Method



Diesel hammer

Suitable Piling Method



Global Construction

Construction Cases

Diesel hammer

Higlight the remarkebles.

Outstanding achievements

01

Patent 01
Piling Equipment Engineering Research Center of Guangdong,China 02
CE Certificate 03
ISO 9001 Certificate 04

02

04

03

Diesel hammer

About Us

Established in 1993, STARKE is China's leading piling equipment manufacturer. We provide high quality piling machine for all kinds of foundation projects, capable from custom design to after-sales services, offering total solutions for customers.

Our main products include: diesel pile hammers, hydraulic impact hammers, hydraulic vibrating hammers, static pile pressing machines, hydraulic crawler piling rigs, foot-step piling rigs and rock breakers.

For 30 years, we will continue dedication on innovative technology,product quality and customer service in our key purpose. Not only we are the market leader of piling hammers in China, our products have also been well sold in international market, with over 30 countries already using STARKE's equipment, throughout North & South America, the Southeast Asia countries, the Middle East countries, Africa and to Europe.

We have obtained the ISO9001 certificate in 2000 and CE certificate for diesel hammers and hydraulic impact hammers.

Hydraulic Impact Hammer

Product Category

Guangdong Liyuan Hydraulic Machinery Co., Ltd.
No.9, Jinxia Road,Hongmei Town,Dongguan City,Guangdong Province,China
+86 769 81830888 81830911
liyuan@starke.com.cn
STARKE
starke-global.com